



TABLE OF SPECIFICATIONS

Fin space 4.1 mm Tubes 1/2"													
Model	Capacity			Surface	Air Flow						Defrost Heaters		Weight
	ΔT=Tamp-Tevap				Fans			Motor			Total Power	No of Elements **	
	6	8	10	Watt*	m2	m3/h	(D) mm	No of fans	Power motor	Amps per motor I	Voltage U (V)		Watt
ORL 12 S	674	1104	1599	6.74	1100	300	1	16/60	0.42	230 50hz	840	2	11
ORL 34 S	967	1572	2110	8.11	1300	300	1	25/90	0.62	230 50hz	840	2	12
ORL 10 S	1149	1792	2388	9.38	1320	300	1	25/90	0.62	230 50hz	980	2	13
ORL 15 S	1733	2507	3310	11.18	2000	300	2	25/90	0.62	230 50hz	1440	2	18
ORL 20 S	1994	3230	4346	16.76	2550	300	2	25/90	0.62	230 50hz	1440	2	20
ORL 21 S	2958	4361	5739	22.33	2700	300	2	25/90	0.62	230 50hz	1440	2	25
ORL 30 S	3802	5466	7040	28.53	4500	300	3	25/90	0.62	230 50hz	2200	2	36
ORL 40 S	4049	6091	8005	34.23	3700	300	3	39/85	0.42	230 50hz	2200	2	40
ORL 50 S	5907	8735	11500	44.29	7100	300	4	39/85	0.42	230 50hz	3400	2	51
ORL 75 S	7006	10166	13213	53.14	7000	300	4	39/85	0.42	230 50hz	3400	2	60
ORL 100 S	10131	14380	18600	70.65	8530	350	4	70/128	0.63	230 50hz	4540	2	86

* Room Temperature 0 °C

R134a

R404a

R22

** Optional

1.05

1

1.09

Fin space 6.4 mm Tubes 1/2"													
Model	Capacity			Surface	Air Flow						Defrost Heaters		Weight
	ΔT=Tamp-Tevap				Fans			Motor			Total Power	No of Elements **	
	6	8	10	Watt*	m2	m3/h	(D) mm	No of fans	Power motor	Amps per motor I	Voltage U (V)		Watt
ORL 12 C	663	966	1361	4.46	1320	300	1	25/90	0.62	230 50hz	1260	3	11
ORL 34 C	730	1128	1684	5.38	1300	300	1	25/90	0.62	230 50hz	1260	3	12
ORL 10 C	899	1440	1995	6.22	1320	300	1	25/90	0.62	230 50hz	1440	3	13
ORL 15 C	1270	2015	2569	7.41	2600	300	2	25/90	0.62	230 50hz	2160	3	18
ORL 20 C	1805	2620	3683	11.12	2700	300	2	39/85	0.42	230 50hz	2160	3	22
ORL 21 C	2137	3449	4448	14.83	2650	300	2	39/85	0.42	230 50hz	2160	3	27
ORL 30 C	3055	4335	5432	18.93	4100	300	3	39/85	0.42	230 50hz	3300	3	36
ORL 40 C	3038	4861	6396	22.7	4000	300	3	39/85	0.42	230 50hz	3300	3	44
ORL 50 C	4214	6879	8959	29.38	8000	350	3	70/128	0.63	230 50hz	5100	3	53
ORL 75 C	5321	7964	10030	35.25	6500	350	3	70/128	0.63	230 50hz	5100	3	60
ORL 100 C	7628	11548	14580	46.97	8650	350	4	70/128	0.63	230 50hz	6810	3	90

* Room Temperature -18 °C

R134a

R404a

R22

0.86

1

0.96