



TABLE OF SPECIFICATIONS

| Fin space 3.8 mm Tubes 3/8" | | | | | | | | | | | | | |
|-----------------------------|---------------|------|------|---------|----------------|-------------------|-----------|------------|-----------------|------------------|-----------------|----------------|--------|
| Model | Capacity | | | Surface | Air Flow | | | | | | Defrost Heaters | | Weight |
| | ΔT-Temp-Tevap | | | | Fans | | | Motor | | | Total Power | No of Elements | |
| | 0 | 8 | 10 | Watt* | m ² | m ³ /h | (D) mm | No of fans | Power per motor | Amps per motor l | Voltage U (V) | | Watt |
| OR 14 S | 236 | 391 | 505 | 1,9 | 290 | 200 | 1 | 3\29 | 0,19 | 230 50hz | - | - | 3,7 |
| OR 13 S | 432 | 692 | 895 | 2,7 | 480 | 250 | 1 | 10\36 | 0,25 | 230 50hz | - | - | 5,2 |
| OR 12 S | 547 | 854 | 1182 | 3,0 | 400 | 250 | 1 | 10\36 | 0,25 | 230 50hz | - | - | 5,9 |
| OR 34 S | 699 | 1195 | 1744 | 5,3 | 710 | 300 | 1 | 16\60 | 0,42 | 230 50hz | - | - | 7,7 |
| OR 13 D | 425 | 711 | 916 | 2,6 | 550 | 250 | 1 | 10\36 | 0,25 | 230 50hz | - | - | 5,2 |
| OR 12 D | 541 | 885 | 1178 | 3,0 | 540 | 250 | 1 | 10\36 | 0,25 | 230 50hz | - | - | 6,2 |
| OR 34 D | 721 | 1232 | 1883 | 5,3 | 810 | 300 | 1 | 16\60 | 0,42 | 230 50hz | - | - | 7,6 |
| OR 10 D | 792 | 1458 | 1985 | 6,4 | 980 | 300 | 1 | 25\90 | 0,62 | 230 50hz | - | - | 9 |

* Room Temperature 0 °C

R134a 1,05 R404a 1 R22 1,09

DIMENSION TABLE

| Model | Dimensions | | | | | | | | Connection | | Tube | Sound Pressure |
|---------|------------|-----|-----|-----|-----|----------|-----|-------|------------|--------|--------|----------------|
| | B | H | F | L | A | Suspensi | E | Drain | Input | Output | Volume | dB/5m |
| | mm | mm | mm | mm | mm | ons | mm | mm | in | in | ltr | |
| OR 14 S | 435 | 445 | 110 | 240 | 85 | 4 | 322 | 17 | 3/8" | 3/8" | 0,45 | - |
| OR 13S | 435 | 565 | 140 | 285 | 70 | 4 | 322 | 17 | 3/8" | 1/2" | 0,75 | - |
| OR 12 S | 435 | 565 | 140 | 285 | 70 | 4 | 322 | 17 | 3/8" | 1/2" | 0,92 | - |
| OR 34 S | 435 | 745 | 170 | 390 | 100 | 4 | 322 | 17 | 1/2" | 5/8" | 1,32 | - |
| OR 13 D | 435 | 565 | 140 | 240 | 115 | 4 | 322 | 17 | 3/8" | 1/2" | 0,75 | - |
| OR 12 D | 435 | 745 | 140 | 285 | 185 | 4 | 322 | 17 | 3/8" | 1/2" | 0,92 | - |
| OR 34 D | 435 | 745 | 170 | 285 | 185 | 4 | 322 | 17 | 1/2" | 5/8" | 1,32 | - |
| OR 10 D | 435 | 745 | 170 | 390 | 185 | 4 | 322 | 17 | 1/2" | 5/8" | 1,65 | - |

