




INDUSTRIAL EQUIPMENT

MEDIUM TEMPERATURE AND HIGH RELATIVE HUMIDITY KPMH



Compact / Split

In compact units,
only A2L refrigerant
is available.



GENERAL CHARACTERISTICS

- Electronic expansion valve.
- Control of equipment operation by automaton.
- 5.7" touch screen.
- Specially designed for vegetables, long-term fruit storage and meat blast chillerà.
- Thanks to a larger evaporating surface than the KPM models, maintains a higher relative humidity in the cold room.
- Defrosting by hot gas up to 22 HP.
- Fin pitch = 5 mm.
- Larger surface area in evaporator coil.
- High RH in the room.
- Smaller ΔT .
- Models with two evaporators have electrical defrosting.

KIDEPACK

Model	Refrigeration capacity	Compressor	Max. absorbed powerl	Box	Evaporator	Air flow
R-455A R-449A	Watts	HP	kW	Cond. / Evap.	m³/h	m
KPMH-3	5.700	3 H	5,00	145	5.600	17
KPMH-4	8.000	4 H	5,80	150	7.900	19
KPMH-5	10.300	5 H	7,20	150	7.900	19
KPMH-6	14.100	6 H	10,50	250	16.200	20
KPMH-8	16.600	8 H	11,90	250	16.200	20
KPMH-10	21.400	10 H	14,30	250	16.200	20
KPMH-13	26.500	13 H	19,20	350	25.100	22
KPMH-15	29.300	15 H	18,20	350	25.100	22
KPMH-20	34.500	20 SH	21,00	350	25.100	22
KPMH-22	39.600	20 SH	22,60	350	27.000	25
KPMH-25-s	44.200	25 SH	27,70	450 / 2 x 250	32.400	20
KPMH-30-s	50.100	30 SH	31,80	450 / 2 x 350	50.200	22
KPMH-35-s	65.200	35 SH	39,00	450 / 2 x 350	50.200	22
KPMH-40-s	75.100	40 SH	44,10	450 / 2 x 350	54.000	25