




INDUSTRIAL EQUIPMENT

LOW TEMPERATURE KPB



Compact / Split

In compact units,
only A2L refrigerant
is available.



R-454C R-449A
R-455A



GENERAL CHARACTERISTICS

- Electronic expansion valve.
 - Control of equipment operation by automaton.
 - 5.7" touch screen.
 - Suitable for the preservation of frozen products in general.
 - Hot gas defrosting up to 40 HP.
 - Evaporator fin pitch = 5 mm.
 - Cooling capacity up to 65.600 W.
 - High C.O.P.
 - Models with two evaporators have electrical defrosting.
 - Possibility of R-452A.
- For chambers between -22/-25 °C with A2L refrigerants consult the technical office.

KIDEPACK

Model	Refrigeration capacity	Compressor	Max. absorbed powerl	Box	Evaporator	Air flow
R-455A R-449A	Watts	HP	kW	Cond. / Evap.	m³/h	m
KPB-3	4.200	3 SH	5,10	145	5.600	17
KPB-4	5.100	4 SH	6,10	145	5.600	17
KPB-5	6.200	5 SH	7,00	145	5.600	17
KPB-7	7.200	6 SH	8,10	150	7.900	19
KPB-8	9.100	9 SH	9,40	150	7.900	19
KPB-10	10.400	12 SH	9,70	150	7.900	19
KPB-15	15.700	15 SH	18,00	250	16.200	20
KPB-20	18.700	20 SH	20,40	250	16.200	20
KPB-25	23.400	25 SH	24,80	250	16.200	20
KPB-30	27.900	30 SH	31,20	350	25.100	22
KPB-40	33.100	40 SH	36,50	350	25.100	22
KPB-50-s	46.300	50 SH *	48,60	450 / 2 x 250	32.400	20
KPB-60-s	55.200	60 SH *	60,80	450 / 2 x 350	50.200	22
KPB-80-s	65.600	80 SH *	69,60	450 / 2 x 350	50.200	22

* With two compressors